



## VLMB01

Mounting Base \ 30-500MHz

### **Electrical Specifications:**

|                        |             |
|------------------------|-------------|
| <u>Frequency band</u>  | 30-500MHz   |
| <u>VSWR</u>            | $\leq 1.4$  |
| <u>Max.input power</u> | 100watts    |
| <u>Input impedance</u> | 50 $\Omega$ |

### **Mechanical Specifications:**

|                               |                               |
|-------------------------------|-------------------------------|
| <u>Mount connector</u>        | NMO female                    |
| <u>Cable length</u>           | 5m or customized              |
| <u>RF connector interface</u> | TNC male or customized        |
| <u>Mounting way</u>           | 5/8 " -11UNC screw connecting |

### **Environmental Specifications:**

|                          |                 |
|--------------------------|-----------------|
| <u>Operating Tempt.</u>  | -40°C to + 60°C |
| <u>Relative Humidity</u> | Up to 100%      |

### **Dimension & weight:**

|                           |                              |
|---------------------------|------------------------------|
| <u>Dimension</u>          | $\Phi 69 \times 41\text{mm}$ |
| <u>Net   Gross weight</u> | 0.33kg   0.4kg               |
| <u>Shipping Package</u>   | 25units/carton               |
| <u>Packed dimensions</u>  | 47*40*23.5cm                 |
| <u>Shipping weight</u>    | 12kg                         |

### **Outline drawing:**

